



BOLDEN EMULSION PRIMER WATER BASE

BOLDEN

BOLDEN BE has been produced to meet the requirements of ASTM D 1187.

PACKAGING
18 LITRE PER PAILS

PRODUCT DESCRIPTION

BOLDEN WB is a brushable, water-based sulphate resistant bitumen coating. It is formed by the anionic emulsification of pliable bitumen and is both stable and easy to apply. It adheres to all types of surfaces and can also be diluted to become a penetrating priming coat for use on porous surfaces.

ADVANTAGES

- Waterproof & Weather proof.
- Anti corrosive
- Environment friendly
- Non-flammable
- Excellent resistance to UV rays, mild acids and alkalis

PRINCIPAL APPLICATIONS

BOLDEN WB can be used:

- as a general purpose damp proof coating for concrete.
- as a waterproofing and protective coating for basements, foundations and retaining walls.
- as a vapor barrier for both above and below ground applications.
- as a maintenance coating for roofs and walls over concrete or metal surfaces.
- as a bonding and priming coat for a variety of bitumen-based waterproofing systems, whether liquid, felts or membranes. as an excellent anti-corrosion paint for metal surfaces

APPLICATION INSTRUCTION

Application of **BOLDEN WB** can be done with a brush, broom or squeegee on horizontal surfaces. Before application **BOLDEN WB** must be thoroughly stirred.

Surface Preparation

Ensure that surface to be treated is sound and free from all oil, grease and other foreign matters. Cracks, potholes and honey combs are to be repaired with a suitable material from the range of repair mortars.

As a Priming Coat

BOLDEN WB can be diluted up to 1:1 in fresh clear water. Allow 2 to 4 hours for drying before applying the membrane.

As a Liquid System

The first coat to be applied as a priming coat. Allow 2 to 4 hours for drying, then apply a second coat on the prepared surface. If the surface is to be topped with concrete, it is recommended that it should be lightly sprinkled with sand as soon as it is laid, which will act as a protective layer. Excess sand should be brushed off prior to laying the screed.

STORAGE

Reseal containers after use.

Storage Life: Varies with product and climatic conditions but is usually in excess of twelve months. Keep out of direct sunlight. Clean Brushes / Rollers with white spirit or paraffin after use or discard safely.

HEALTH & SAFETY

As with all construction chemical products, caution should always be exercised. clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swollen, do not induce vomiting, but call for medical assistance immediately.

BOLDEN WB is tested at random intervals by independent laboratories to international standards and the results of these tests are available on request. In addition, each batch manufactured is subject to strict quality control procedures to ensure it meets appropriate and applicable standards and/or norms.

TYPICAL PROPERTIES

PROPERTY METHOD	TYPICAL VALUE	TEST METHOD
Colour	brown dries to black	-
Density @ 25°C, min, kg/L	0.99	ASTM D 244
Viscosity@ 25°C	20-100	ASTM D 88/ASTM D 244
Flexibility, Clh at 25°C)	No cracking	ASTM D 1187
Service temperature	-10°C to + 50°C	-
Shelf life	12 months	-
Adhesion to dry surface	Excellent	-
Resistance to UV rays	No erosion or cracking	-
Resistance to dry surface	Excellent	-
Resistance to mild acids and alkalis	Excellent	-
Coverage rate per coat Dilute 1:1	6-10m ² /L	-
Top coat Smooth concrete Metal surface	4-6m ² /L 6-10m ² /L	-
Toxicity	Non-toxic when cured	-
Drying time	Touch dry: 2-4 hours Full dry: 8 hours	-



LOCATIONS

KIGDOM OF SAUDI ARABIA

unitech.ksa@ikkgroup.com

Jeddah

Tel : +966 12 627 8222
Fax: +966 12 627 8722

Jeddah - Ghurab Showroom

Tel : +966 12 667 2000
Fax: +966 12 661 4306

Mak kah/Taif

Tel : +966 12 541 1206
Fax: +966 12 532 1675

Mad inah

Tel : +966 14 842 1095
Fax: +966 14 842 1090

Yanbu

Tel : +966 14 390 1499
Fax: +966 14 322 7101

Khamis Mushayt

Tel : +966 17 237 5929
Fax: +966 17 237 8783

Najran

Tel : +966 17 546 3873
Fax : +966 17 546 3873

Al Baha

Tel : +966 17 237 5929
Fax: +966 17 237 8783

Sharorah

Tel : +966 17 532 8153
Fax: +966 17 532 8153

Gizan

Tel : +966 17 321 6660
Fax: +966 17 321 0665

Riyadh North

Tel : +966 11 415 5465
Fax: +966 11 456 6627

Riyadh South

Tel : +966 11 448 0112
Fax: +966 11 447 7421

Riyadh West

Tel : +966 11 431 6271
Fax: +966 11 431 7642

Riyadh East

Tel : +966 11 448 0112
Fax: +966 11 447 7421

Qassim / Buraidah

Tel : +966 16 382 3946
Fax: +966 16 385 2186

Hail

Tel : +966 16 543 3931
Fax: +966 16 543 3935

Skakah / Qurayyat

Tel : +966 14 626 3904
Fax: +966 14 626 3905

Tabuk

Tel : +966 14 423 5203
Fax: +966 14 423 5203

Hafr el Batin

Tel : +966 13 729 3644
Fax: +966 13 729 3644

Dammam

Tel : +966 13 859 0097
Fax: +966 13 857 8177

Jubail

Tel : +966 13 361 4390
Fax: +966 13 362 4499

Hofuf

Tel : +966 13 530 1474
Fax: +966 13 530 7144

FACTORIES

SFSP - KSA

sfsp.jeddah@ikkgroup.com

Specialized Factory for Steel Products

3rd Industrial City / Jeddah

Tel: +966 12 637 4482
Fax: +966 12 636 1963

SFSP / UAE

sfsp.uae@ikkgroup.com

SIGMA Factory for Steel Products

DIC (Dubai Industrial City)

Tel : +971 4 818 1919

SFSP / Egypt

sfsp.cairo@ikkgroup.com

Specialized Factory for Steel Products

6th of October City Giza

Tel : +20 2 3820 6477
Fax: +20 2 3820 6036

SFSP / Lebanon

sfsp.lebanon@ikkgroup.com

Specialized Factory for Steel Products

Tanayel, Bekaa

Tel: +961 8 514 290
Fax: +961 8 514 291

BAHRAIN

unitech.bahrain@ikkgroup.com

Manama

Tel : +973 17 874 897
Fax: +973 17 789 470

KUWAIT

unitech.kuwait@ikkgroup.com

Kuwait City

Tel : +965 2 4924 937
Fax: +965 2 4924 938

UNITED ARAB EMIRATES

unitech.uae@ikkgroup.com

Dubai - Al Rashidiyah

Tel : +971 4 2591 773
Fax : +971 4 2591 774

Abu Dhabi - Musaffah

Tel: +971 2 552 3393
Fax: +971 2 552 5499

OMAN

unitech.oman@ikkgroup.com

Muscat

Tel : +968 24 591 006
Fax : +968 24 597 006

JORDAN

unitech.jordan@ikkgroup.com

Amman

Tel : +962 6 556 3030
Fax: +962 6 554 7911

Aqaba

Tel : +962 6 556 3030
Fax: +962 6 554 7911

PAKISTAN

unitech.pakistan@ikkgroup.com

Karachi - Clifton

Tel-Fax : +92 21 35826120

EGYPT

unitech.egypt@ikkgroup.com

Cairo 6th of October City

Tel : +20 2 3820 6477
Fax: +20 2 3820 6036

LEBANON

unitech.lebanon@ikkgroup.com

Beirut

Tel : +961 1 858 277
Fax: +961 1 858 276

ENGINEERING, DESIGN, MARKETING & MULTIMEDIA

Unitech Deutschland GmbH

Germany

unitech.germany@ikkgroup.com

Stuttgart

Tel : +49 711 6868 7222
Fax: +49 711 6868 7223

Multi-D s.a.r.l

Lebanon

multi-d@ikkgroup.com

Multi-d Beirut

Tel : +961 1 841 155
Fax: +961 1 841 156

R&D DEPARTMENT

Saih Suhaib-3, Opp DEWA Substation, Dubai Industrial City, Dubai, UAE

Tel : +971 4 818 1944 - Mob: +971 55 517 0841

Email: unitech.uae@ikkgroup.com - abed.demachkieh@ikkgroup.com