



**UNITECH**

Isam Kabbani Group of Companies  
www.unitech-ikk.com | www.unipro-ikk.com

**WATERPROOFING SOLUTIONS**

## WATER BASED, POLYURETHANE LIQUID-APPLIED WATERPROOFING MEMBRANE



**POLY TI**

### POLY TI AQUA

#### PRODUCT DESCRIPTION

The POLY TI AQUA is a liquid-applied, highly permanent elastic, cold applied and cold curing, water based, one component, modified polyurethane membrane used for long-lasting waterproofing.

When the POLY TI AQUA is applied, it forms a hydrophobic, 100% waterproofing, permanent elastic, seamless membrane without joints or leak possibilities, that protect old and new structures efficient and on a long-term basis.

#### USES

- Waterproofing of Roofs
- Waterproofing of Balconies and Terraces
- Waterproofing of Wet-Areas (under tile)
- Waterproofing and protection of Concrete constructions.
- Waterproofing and Protection of Drywall and Cement-boards
- Protection of Polyurethane Foam Insulation

#### PACKAGING

POLY TI AQUA pails should be stored in dry and cool rooms for up to 18 months. Protect the material against frost and direct sunlight. Storage temperature: 5<sup>o</sup>-30<sup>o</sup>C. Products should remain in their original, unopened containers, bearing the manufacturers name, product designation, batch number and application precaution labels.

#### SAFETY MEASURES

Keep away from children. Do not use empty containers for food storage. See information supplied by the manufacturer. Please study the Safety Data sheet. PROFESSIONAL USE ONLY.

#### ADVANTAGES

- Simple application (roller or airless spray).
- When applied forms seamless membrane without joints.
- UV stable.
- Suitable for exposed surfaces.
- Resistant to water.
- Resistant to frost.
- Maintains its mechanical properties over a temperature span of -20°C to +80°C.
- Provides water vapor permeability.
- Full surface adherence without any additional anchoring.
- The waterproofed surface can be walked on (domestic use).
- Even if the membrane gets damaged, it can be easily repaired locally within minutes.
- Low cost

#### CONSUMPTION

1– 1,5 kg/m<sup>2</sup> applied in two or three layers. This coverage is based on application by roller onto a smooth surface in optimum conditions. Factors like surface porosity, temperature and application method can alter consumption. In case of entire area POLY TI FABRIC reinforcement, consumption increases.

#### COLORS

The POLY TI AQUA is supplied in white, grey and terracotta red.

## TECHNICAL DATA

PROPERTY	RESULTS	TEST METHOD
Elongation at Break	>300 %	ASTM D 412
Tensile Strength	>1,5 N/ mm <sup>2</sup>	ASTM D 412
Water Vapor Permeability	>15 gr/m <sup>2</sup> /day	ISO 9932:91
Resistance to Water Pressure	No Leak (1m water column, 24h)	DIN EN 1928
Adhesion to concrete	>1,2 N/mm <sup>2</sup>	ASTM D 903
Hardness (Shore A Scale)	60	ASTM D 2240 (15")
Tack Free Time	6 hours	Conditions: 20°C, 50% RH
Light Pedestrian Traffic Time	18 hours	
Final Curing time	7 days	

## APPLICATION

### Surface Preparation

Careful surface preparation is essential for optimum finish and durability.

The surface needs to be clean, dry and sound, free of any contamination, which may harmfully affect the adhesion of the membrane. Maximum moisture content should not exceed 8%. Substrate compressive strength should be at least 25MPa, cohesive bond strength at least 1.5MPa. New concrete structures need to dry for at least 28 days. Old, loose coatings, dirt, fats, oils, organic substances and dust need to be removed by a grinding machine. Possible surface irregularities need to be smoothed. Any loose surface pieces and grinding dust need to be thoroughly removed.

### Repair of cracks and joints:

The careful sealing of existing cracks and joints before the application is extremely important for long lasting waterproofing results.

- Clean concrete cracks, hairline cracks and joints of dust, residue or other contamination. Fill all prepared cracks and joints with POLY JOINT 30 sealant. Then apply a layer of POLY TI AQUA, 200mm wide centered over all cracks and while wet, cover with a correct cut stripe of the POLY TI FABRIC . Press it to soak. Then saturate the POLY TI FABRIC with enough POLY TI AQUA until it is fully covered. Allow to cure.

### Priming

Prime absorbent and brittle surfaces like concrete, cement screed, mortar, plaster, wood with POLY TI AQUA diluted with 15-20% clean water used as primer. For very brittle surfaces and/or demanding applications prime with POLY TI AQUA. Allow the primer coat to cure.

### Waterproofing membrane

Stir well before using. Poor the POLY TI AQUA onto the prepared and primed surface and lay it out by roller, brush or squeegee, until all surface is covered. You can use airless spray allowing a considerable saving of manpower.

Reinforce always with the POLY TI FABRIC at problem areas, like wall-floor connections, pipes, chimneys, waterspouts (siphon), lightdomes, etc. In order to do that, apply on the still wet POLY TI AQUA a correct cut piece of POLY TI FABRIC , press it to soak, and saturate again with enough POLY TI AQUA. For detailed application instructions with the POLY TI FABRIC , contact our R+D department. We recommend reinforcement of the entire surface, with the POLY TI FABRIC . Use 5-10cm stripe overlapping.

After 18-36 hours apply another layer of the POLY TI AQUA. For better waterproofing results apply a third layer of the POLY TI AQUA.

**WARNING:** Do not apply the POLY TI AQUA in temperatures below 5°C or when dew, rain or frost is imminent in the next 48 hours. For best results, the temperature during application and cure should be between 5°C and 35°C. Low temperatures retard cure while high temperature speed up curing. High humidity (fog or dew conditions) retard cure and affect the curing times and curing properties. Do not apply the POLY TI AQUA over 0.5 mm thickness (dry film) per layer

**WARNING:** The POLY TI AQUA is slippery when wet. In order to avoid slipperiness during wet days, sprinkle suitable aggregates onto the still wet coating to create an anti-slip surface. Please contact our R+D Dept. for more details.

# LOCATIONS

## KIGDOM OF SAUDI ARABIA

unitech.ksa@ikkgroup.com

### Jeddah

Tel : +966 12 627 8222  
Fax: +966 12 627 8722

### Jeddah - Ghurab Showroom

Tel : +966 12 667 2000  
Fax: +966 12 661 4306

### Mak kah/Taif

Tel : +966 12 541 1206  
Fax: +966 12 532 1675

### Mad inah

Tel : +966 14 842 1095  
Fax: +966 14 842 1090

### Yanbu

Tel : +966 14 390 1499  
Fax: +966 14 322 7101

### Khamis Mushayt

Tel : +966 17 237 5929  
Fax: +966 17 237 8783

### Najran

Tel : +966 17 546 3873  
Fax : +966 17 546 3873

### Al Baha

Tel : +966 17 237 5929  
Fax: +966 17 237 8783

### Sharorah

Tel : +966 17 532 8153  
Fax: +966 17 532 8153

### Gizan

Tel : +966 17 321 6660  
Fax: +966 17 321 0665

### Riyadh North

Tel : +966 11 415 5465  
Fax: +966 11 456 6627

### Riyadh South

Tel : +966 11 448 0112  
Fax: +966 11 447 7421

### Riyadh West

Tel : +966 11 431 6271  
Fax: +966 11 431 7642

### Riyadh East

Tel : +966 11 448 0112  
Fax: +966 11 447 7421

### Qassim / Buraidah

Tel : +966 16 382 3946  
Fax: +966 16 385 2186

### Hail

Tel : +966 16 543 3931  
Fax: +966 16 543 3935

### Skakah / Qurayyat

Tel : +966 14 626 3904  
Fax: +966 14 626 3905

### Tabuk

Tel : +966 14 423 5203  
Fax: +966 14 423 5203

### Hafr el Batin

Tel : +966 13 729 3644  
Fax: +966 13 729 3644

### Dammam

Tel : +966 13 859 0097  
Fax: +966 13 857 8177

### Jubail

Tel : +966 13 361 4390  
Fax: +966 13 362 4499

### Hofuf

Tel : +966 13 530 1474  
Fax: +966 13 530 7144

## FACTORIES

### SFSP - KSA

sfsp.jeddah@ikkgroup.com

Specialized Factory for Steel Products

#### 3rd Industrial City / Jeddah

Tel: +966 12 637 4482  
Fax: +966 12 636 1963

### SFSP / UAE

sfsp.uae@ikkgroup.com

SIGMA Factory for Steel Products

#### DIC (Dubai Industrial City)

Tel : +971 4 818 1919

### SFSP / Egypt

sfsp.cairo@ikkgroup.com

Specialized Factory for Steel Products

#### 6th of October City Giza

Tel : +20 2 3820 6477  
Fax: +20 2 3820 6036

### SFSP / Lebanon

sfsp.lebanon@ikkgroup.com

Specialized Factory for Steel Products

#### Tanayel, Bekaa

Tel: +961 8 514 290  
Fax: +961 8 514 291

## BAHRAIN

unitech.bahrain@ikkgroup.com

### Manama

Tel : +973 17 874 897  
Fax: +973 17 789 470

## KUWAIT

unitech.kuwait@ikkgroup.com

### Kuwait City

Tel : +965 2 4924 937  
Fax: +965 2 4924 938

## UNITED ARAB EMIRATES

unitech.uae@ikkgroup.com

### Dubai - Al Rashidiyah

Tel : +971 4 2591 773  
Fax : +971 4 2591 774

### Abu Dhabi - Musaffah

Tel: +971 2 552 3393  
Fax: +971 2 552 5499

## OMAN

unitech.oman@ikkgroup.com

### Muscat

Tel : +968 24 591 006  
Fax : +968 24 597 006

## JORDAN

unitech.jordan@ikkgroup.com

### Amman

Tel : +962 6 556 3030  
Fax: +962 6 554 7911

### Aqaba

Tel : +962 6 556 3030  
Fax: +962 6 554 7911

## PAKISTAN

unitech.pakistan@ikkgroup.com

### Karachi - Clifton

Tel-Fax : +92 21 35826120

## EGYPT

unitech.egypt@ikkgroup.com

### Cairo 6<sup>th</sup> of October City

Tel : +20 2 3820 6477  
Fax: +20 2 3820 6036

## LEBANON

unitech.lebanon@ikkgroup.com

### Beirut

Tel : +961 1 858 277  
Fax: +961 1 858 276

## ENGINEERING, DESIGN, MARKETING & MULTIMEDIA

### Unitech Deutschland GmbH

#### Germany

unitech.germany@ikkgroup.com

### Stuttgart

Tel : +49 711 6868 7222  
Fax: +49 711 6868 7223

### Multi-D s.a.r.l

#### Lebanon

multi-d@ikkgroup.com

### Multi-d Beirut

Tel : +961 1 841 155  
Fax: +961 1 841 156

## R&D DEPARTMENT

Saih Suhaib-3, Opp DEWA Substation, Dubai Industrial City, Dubai, UAE

Tel : +971 4 818 1944 - Mob: +971 55 517 0841

Email: unitech.uae@ikkgroup.com - abed.demachkieh@ikkgroup.com